



(19)

(11) Publication number:

063

Generated Document.

PATENT ABSTRACTS OF JAPAN(21) Application number: **05105264**(51) Intl. Cl.: **G06F 15/403 G06F 12/00**(22) Application date: **06.05.93**


<p>(30) Priority:</p> <p>(43) Date of application publication: 08.11.94</p> <p>(84) Designated contracting states:</p>	<p>(71) Applicant: HITACHI LTD</p> <p>(72) Inventor: SAEGUSA TAKASHI Ooba MICHIKO</p> <p>(74) Representative:</p>
---	--

(54) DATA BASE DISPLAY METHOD

(57) Abstract:

PURPOSE: To carry out the reception processing of the result of access given to a data base in parallel to the display processing where the data on the access result is shown on a screen by securing the independent operations between a control means which has an access to the data base and a display means which shows the data on the access result on a screen while receiving the processing state of the control means.

CONSTITUTION: A main processing part 201 decides whether its access subject data base is equal to a local data base 105 of a local computer 101 or a remote data base 109 of a remote computer 106. When the data base 109 is decided, the access request of a user is transmitted to a remote server processing part 107. Then the access result is received by the part 201 via



the part 107. Meanwhile a data base control part 104 retrieves the data base 105 when the local data base is decided by the part 201. Then the part 201 stores the retrieving result in a local file 207 and then set the result into a main shared memory 203 for display if it is equivalent to a single screen.

COPYRIGHT: (C)1994,JPO



(19)

(11) Publication number: **101**

Generated Document.

PATENT ABSTRACTS OF JAPAN

(21) Application number: **08347824**(51) Intl. Cl.: **G06F 11/28 G06F 11/34 G06F**(22) Application date: **26.12.96**

(30) Priority:

(43) Date of application publication: **21.07.98**

(84) Designated contracting states:

(71) Applicant: **NEC CORP**(72) Inventor: **KIKUCHI SHINJI**


(74) Representative:

(54) METHOD AND DEVICE FOR EVALUATING HIGH-LOAD EMULATION PERFORMANCE


(57) Abstract:

PROBLEM TO BE SOLVED: To improve accuracy in evaluation without requiring any special equipment for evaluating the performance of a server computer system.

SOLUTION: A structured query language(SQL) sentence and a data definition language(DDL) sentence are taken out of a computer aided software engineering(CASE) tool repository 3 and based on the procedure of server constructing system, a measurement environment is automatically generated at a server computer system 8 to be measured. Based on the procedure of work load preparing system for performing a load test, a measurement transaction is semiautomatically generated and the measurement transaction



the measurement transaction prepared based on the procedure of work load preparing system is continuously applied to the server computer system 8 to be measured. Then, the change of performance evaluation value is measured by a black box measuring system, a simultaneous processing number to be simultaneously processed through simple probability calculation different from a model due to a queue network is estimated, and the experimentation of comparison with data for evaluation required for performance evaluation possessed through the black box measuring system is tried finite times by a simulation evaluating system.



COPYRIGHT: (C)1998,JPO



(19)

(11) Publication number:

083.

Generated Document.

PATENT ABSTRACTS OF JAPAN(21) Application number: **07138309**(51) Intl. Cl.: **H04L 12/42 H04L 29/14**(22) Application date: **05.06.95**

(30) Priority:

(43) Date of application
publication: **13.12.96**(84) Designated contracting
states:(71) Applicant: **MITSUBISHI ELECTRIC**(72) Inventor: **TOBA JUN**
NAKAMURA MASATO

(74) Representative:

(54) DATA TRANSMITTER

(57) Abstract:

PURPOSE: To suppress the load on a station and to guarantee the timewise continuity of cyclic data when the simulation of process data is performed for the maintenance and adjustment in a distributed processing process control system.

CONSTITUTION: In each station 9, a cyclic transmission memory 6a extending transmission data and a cyclic reception memory 6b extending received data are provided. Data to be simulated from the station 9 to be simulated is once transmitted to the station 9 to be simulated. In the station 9 to be simulated, data for which a broadcast transmission to all the stations is to be performed is worked.

COPYRIGHT: (C)1996,JPO

